



Report Number: 70579 Date: 02-13-2015

CERTIFICATE OF TESTING

For the Account Of:	Indetex NV Torkonjestraat 21/c 8510 Marke					
Contact:	Belgium Mr. Phillipe Debie					
Client's Identification:	Delfino / Fenice					
TEST PERFORMED	NFPA 701 Standard	Methods of Fire T	est for Flame Prop	agation of Textiles an	d Films 2010 – Test	#1
TEST RESULTS						
Specimen	Initial Mass	Final Mass	Mass Loss	Flaming Drip	Afterflame	
·	(g)	(g)	(%)	(s)	(s)	
1	15.7	11.5	27%	0	0	
2	15.7	11.5	27%	0	0	
3	15.3	10.9	28%	0	0	
4	15.2	10.9	28%	0	0	
5	15.3	10.9	29%	0	0	
6	15.4	10.9	29%	0	0	
7	15.4	11.0	28%	0	0	
8	15.5	12.3	20%	0	0	
9	15.5	10.4	33%	0	0	
10	15.5	10.6	32%	0	0	
Average Approximate weight (oz./	15.4 'sq. yd): 7.6	11.1	28%	0.0	0.0	
Product Configuration: Conditioning: Intended End-use (if kno	Oven at 220°F for m		s	5 ±2%RH for minimum	24 hours	
ACCEPTANCE CRITERIA Afterflame is required to b 1. Where fragments seconds per spec	e recorded; however, it is it is or residues of specimens cimen for the sample of 10	that fall to the floor	r of the test chamber	continue to burn for me	ore than an average of Drip)	2

2. Where the average weight loss of the 10 specimens in a sample is greater than 40 percent, the material shall be recorded as failing.

4. Where the specimens do not demonstrate performance in accordance with either of the conditions indicated above, the material

☐ Does Not Comply
☐ Testing of 10 additional specimens is required

shall be recorded as passing this test and shall be designated as flame resistant.

Based on the above Results and Acceptance Criteria, the item tested:

3. Individual specimens will be listed as a failure if it exceeds mean + 3 SD

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Authorized Signature-MB

CONCLUSION

□ Complies